

## YZ Submersible slurry pump

### Technique parameters

Model	Flow rate		Head	Speed	Efficiency	Motor power
	m <sup>3</sup> /h	L/S	(m)	(RPM)	(%)	(KW)
50YZ50-20	25	6.9	12	1430	39.5	3
80YZ50-10	30	8.3	16	970	24	7.5
50YZ50-20	40	11	22	1440	41	7.5
65YZ50-12	50	13.8	12	1440	55.9	5.5
65YZ50-12A	60	15.8	9.7	1440	55.2	5.5
80YZ80-20B	80	22.2	13.4	1460	51	7.5
80YZ80-20A	90	25	15.6	1460	51	11
80YZ80-20	100	27.2	18	1460	53	11
100YZ100-30A	110	30.6	24	1470	54	18.5
100YZ100-30	120	33.3	28	1470	56	22
100YZ120-60A	130	36.1	16	1480	50	45
100YZ160-38	160	44.4	39	1480	52	45
150YZ250-40B	200	55.6	25	1480	50	37
150YZ250-40	250	69.4	40	1480	52	55

YZ Submersible slurry pump is with structure of vertical single stage and single suction system overhung centrifugal pump, it is made of abrasion-resistant alloy, it can convey medium with high concentration particle. There is no bearing and Gland Seal between impeller and pump body, so the slurry pump is maintenance-free and high temperature resistance, the slurry pump is the ideal centrifugal pump for. OGEM Equipment is professional manufacturer on submersible slurry pump with high quality and economical cost .





## Contact OGEM Equipment



**Professional for mud process**

**Company name:** No.2 Jingxi Road,Lunan District,Tangshan city,Hebei province,China  
(OGEM Equipment)

**Address:** No.1 Nanhua Road, Jiaoda Industrial Park, Lunan District, Tangshan

**Tel:** +86-315-8676484/ 8676483

**Fax:** +86-315-2648099 +86-315-2648088

**Email:** [info@ogemsolidscontrol.com](mailto:info@ogemsolidscontrol.com)

**Website:** <http://www.ogemsolidscontrol.com/>