

Drilling mud centrifugal pump

SB series centrifugal pump is the ideal equipment to provide impetus for Desander 、 Desilter and Jet Mud Mixer. It can also be used as Charge Pump auxiliary perfusion for mud pump and Trip Pump for drilling well head. Centrifugal pump is also called sand pump. We considered completely the set equipment can work in excellent condition in the process of designing parameters). Most parts can be exchanged , with convenient operation and maintenance、 less seal leakage、 reliability、 long life and other advantages.



Drilling mud centrifugal pump Technique parameters 1

Model	Motor (KW)	Flow rate (m ³ /h)	Head (m)	Efficiency (%)	Electric system
SB8×6-14	75	256	43	64	380V/50Hz
		320	40	65	
		416	35	64	
SB8×6-12		335	43	66	460V/60Hz
SB8×6-13	55	232	35	60	380V/50Hz
		290	33	64	
		377	28	65	
SB6×5-12		196	48	61	460V/60Hz
SB6×5-13	45	144	37	57	380V/50Hz
		180	34	60	
		234	29	55	
SB5×4-14		149	61	58	460V/60Hz
SB6×5-12	37	128	32	57	380V/50Hz
		160	30	60	
		208	25	57	
SB5×4-12		112	45	58	460V/60Hz

Drilling mud centrifugal pump Technique parameters 2

Model	Motor (KW)	Flow rate (m ³ /h)	Head (m)	Efficiency (%)	Electric system
SB6×5-11	30	160	23	59	380V/50Hz
		200	21	62	
		260	20	62	
SB5×4-11		112	37	57	460V/60Hz
SB5×4-12	22	72	32	56	380V/50Hz
		90	30	56	
		117	27	55	
SB5×4-10		105	30	57	460V/60Hz
SB5×4-11	18.5	72	26	55	380V/50Hz
		90	24	56	
		117	21	53	
SB4×3-12		55	46	48	460V/60Hz
SB4×3-13	15	40	42	46	380V/50Hz
		50	40	48	
		65	36	53	
SB4×3-11		54	35	47	460V/60Hz

Drilling mud centrifugal pump Technique parameters 3

Model	Motor (KW)	Flow rate (m ³ /h)	Head (m)	Efficiency (%)	Electric system
SB4×3-12	11	36	32	46	380V/50Hz
		45	30	47	
		58.5	27	51	
SB3×2-12		28	45	40	460V/60Hz
SB3×2-12	7.5	40	26	46	380V/50Hz
		45	24	46	
		57	21	49	
SB3×2-11		25	35	41	460V/60Hz
SB3×2-11	5.5	16	25	38	380V/50Hz
		20	23	39	
		26	20	38	

Contact OGEM Equipment



Professional for mud process

Company name: No.2 Jingxi Road,Lunan District,Tangshan city,Hebei province,China
(OGEM Equipment)

Address: No.1 Nanhua Road, Jiada Industrial Park, Lunan District, Tangshan

Tel: +86-315-8676484/ 8676483

Fax: +86-315-2648099 +86-315-2648088

Email: info@ogemsolidscontrol.com

Website: <http://www.ogemsolidscontrol.com/>