


JBQ Mud agitator/mixer

Technique parameters

Model	LJB2.2	LJB5.5	LJB7.5	LJB11	LJB15
Motor	2.2KW (3hp)	5.5KW(7.5hp)	7.5KW(10hp)	11KW(15hp)	15KW(20hp)
Shaft length	According to tank size and client's requirement				
Impeller type	Canted or turbine blade				
Impeller layer	Double or single				
Impeller diameter	400-Ø1200mm				
Speed	63RPM				
Remark	When shaft length exceeds 1.7m, there will be stabilizer				

JBQ series mud Agitator, Less than 5.5 kW drilling mud Agitator adopts the blender cycloid speed reducer, and it is applied to the drug liquids mixing tank. This mud agitator has the advantage of compact structure so it occupies small area. More than 7.5 kW Mud Agitator uses the turbo and worm gear speed reducer, with the large torque transmission、 the revolution is steady it works reliable and has great merit. Common model of mud agitator is JBQ5.5kW 、 JBQ7.5kW 、 JBQ11kW and JBQ15kW . The drilling mud agitator is an important components for OGEM Solids Control drilling fluids processing system. so you have any other questions or need more info on LJB agitator please contact OGEM.



Contact OGEM Equipment



Professional for mud process

Company name: No.2 Jingxi Road,Lunan District,Tangshan city,Hebei province,China
(OGEM Equipment)

Address: No.1 Nanhua Road, Jiaoda Industrial Park, Lunan District, Tangshan

Tel: +86-315-8676484/ 8676483

Fax: +86-315-2648099 +86-315-2648088

Email: info@ogemsolidscontrol.com

Website: <http://www.ogemsolidscontrol.com/>