

FLQ Poor boy degasser/Mud gas separator

Technique parameters

Model	FLQ 800	FLQ1000	FLQ1200
Vessel diameter	Ø800mm	Ø1000mm	Ø1200mm
Treating capacity	240m ³ /h	300m ³ /h	380m ³ /h
Feed inlet	5"	5"	5"
Fluid discharge	8"	10"	10"
Vent line	8"	8"	8"
Weight	1650kg	2000kg	3200kg
Dimension	1900×1900×5700mm	2000×2000×5860mm	2200×2200×6634mm

FLQ **Poor boy degasser** is one kind of drilling fluid equipment. It mainly get rid of invaded gas and remove large pocket of gas to keep well drilling and rig safe. As we said mud/gas separators and degassers mechanically remove entrained gases such as hydrogen sulfide, carbon dioxide and natural gas from the mud system. Entrained gas can reduce the hydrostatic head of the mud column and can cause catastrophic well control problems. OGEM equipment is professional manufacturer on high quality degassers including mud gas separator and gas buster. The quality and standard is according to ISO9001-2000. Find more oil and gas mud equipments at OGEM





Contact OGEM Equipment



Professional for mud process

Company name: No.2 Jingxi Road,Lunan District,Tangshan city,Hebei province,China
(OGEM Equipment)

Address: No.1 Nanhua Road, Jiaoda Industrial Park, Lunan District, Tangshan

Tel: +86-315-8676484/ 8676483

Fax: +86-315-2648099 +86-315-2648088

Email: info@ogemsolidscontrol.com

Website: <http://www.ogemsolidscontrol.com/>